

Countertop & Mobile Printers DATA SHEET





Product Name:

AC MP2

AC MP3

AC CP

Product Category:

Mobile Printers

Countertop Printer

PRODUCT OVERVIEW

AnywhereCommerce introduces its versatile lineup of mobile and desktop thermal printers, designed to meet the demands of modern businesses. Whether for mobile transactions, retail environments, or high-volume printing needs, our printers deliver superior performance, durability, and seamless connectivity. The AC MP2, AC MP3, and AC CP offer a range of solutions from compact mobile printing to high-speed desktop output, ensuring efficiency and reliability in any setting.



KEY FEATURES

Versatile Printing Solutions – The **AC MP2** is a compact mobile printer, the **AC MP3** offers a wider printing width, and the AC CP is a high-speed desktop printer for high-volume needs.

Seamless Connectivity – USB, Bluetooth, Wi-Fi, and LAN/GPRS (**AC CP**) ensure reliable connections across multiple platforms.

Durability & Reliability – IP54 ratings on mobile models, 1.2m drop testing, and up to 150km print life make these printers built to last.

Efficient Paper Handling – Easy-loading mechanisms, multiple paper size support, and an auto-cutter (*AC CP*) optimize workflow and reduce downtime.



CONTACT US



Address: 1100 W Shaw Ave #122
Fresno, CA 93711
E-mail:

E-IIIdil

sales@anywherecommerce.com www.anywherecommerce.com



This document is provided for informational purposes only. All features and specifications are subject to change without notice. The AnywhereCommerce logo is either a trademark or a registered trademark.

Other trademarks and trade names are those of their respective owners.
© 2025 Anywhere Commerce. All rights reserved.

SPECIFICATIONS:

Feature	AC MP2- 2" Mobile Printer	AC MP3- 3" Mobile Printer	AC CP- Countertop Printer
Printing System	Direct Thermal Printer	Direct Thermal Printer	Direct Thermal Printer
Resolution	203 x 203 dpi	203 x 203 dpi	203 x 203 dpi
Printing Speed	80 mm/sec	80 mm/sec	200 mm/sec
Printing Width	48 mm (384 dots)	72 mm (576 dots)	80 mm (640 dots)
Paper Width	58 mm	80 mm	82 & 58 mm
Max Roll Diameter	45 mm	50 mm	102 mm
Printable Fonts	Font A (12 x 24 dots, 32 chars/line), Font B (9 x 16 dots, 42 chars/line)	Font A (12 x 24 dots), Font B (9 x 16 dots)	Font A (12 x 24 dots), Font B (9 24 dots), Font C (8 x 16 dots)
Printable Barcodes	Codabar, Code 128, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, GS1 DataBar, PDF417, Micro PDF417, QR Code, Data Matrix	Codabar, Code 128, EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, GS1 DataBar, PDF417, Micro PDF417, QR Code, Data Matrix	1D: EAN-13, EAN-8, Code 39, Code 128, Interleaved 2 of 5, Codabar
Post Printing Features	N/A	N/A	Auto Cutter
Display Screen	128 x 64 px OLED	OLED	Graphic LCD (128 x 32 px, 4 lines x 22 characters, LED backlight)
Connectivity	USB Optional BlueTooth 4.2 LE Optional BlueTooth 5.1 LE Optional WiFi 802.11 b/g/n	USB Optional BlueTooth 4.2 LE Optional WiFi 802.11 b/g/n	USB 2.0, RS-232C, LAN 100Mbps Cash Drawer through RJ11 External Display through RJ11 Optional GPRS Module SAM slot
Battery	3.7V, 2100mAh Li-lon	7.4V, 2000mAh Li-lon	AC Powered (24V, 2.1A)
Power Supply	DC 5V via USB/contact pins	AC 100-240V, DC 9V, 1.3A	AC 100-240V, DC 24V, 2.1A
Durability	50 km print life, IP54, 1.2m drop tested	50 km print life, IP54, 1.2m drop tested	150km print life, 1.5M auto-cuts
LED Indicators	Battery low, Charging, Paper end, Cover open, Overheating, Bluetooth connection	Paper end, Cover open, Overheating	Paper end, Cover open
Audio Features	N/A	Electromagnetic buzzer	N/A
Controls	On/Off switch, two navigation buttons	On/Off switch, two navigation buttons	On/Off Switch, Feed Button, and four function buttons
Smart Card Reader	Optional (Friction Type)	N/A	N/A
Dimensions (mm)	83 x 112 x 58	106 x 122 x 61	150 x 185 x 130
Weight	260 g	370 g	1700 g
OS Compatibility	iOS, Android, Windows	iOS, Android, Windows	N/A
Accessories	Belt clip, Holster2.0	Belt clip	N/A
Certificates	CE, FCC	CE, FCC, VCCI	CE
Operational Temperature	-10 to 50°C, 20 to 80% RH	-10 to 50°C, 20 to 80% RH	-10 to 40°C, 35 to 85% RH
Storage Temperature	-20 to 60°C, 10 to 90% RH	-20 to 60°C, 10 to 90% RH	-20 to 60°C, 10 to 90% RH
Storage Temperature	-20 to 60°C, 10 to 90% RH	-20 to 60°C, 10 to 90% RH	-20 to 60°C, 10 to 90% RH